JIL 0 1 2005 EEE CLAIMS LISTING -MARKED UP VERSION

Appl. #:

10/657,225

Applicant:

MC Ilvenna, Ryan

Filing date:

09/09/2003

### Claim 1 (currently amended)

A fastener-gripping tool comprising:

- a. a primary and secondary member, both having a handle,
- b. a nail pulling central portion,
- c. a pair of gripping ends,
- d. a claw at each said end,
- e. auto-centering and auto-sizing means,

# Claim 2 (currently amended)

The fastener-gripping tool of claim 1 wherein said primary and secondary members are hinged together at a central area thereby providing a rotary motion pivoting at said central area for aligning the claws at each extremity of the gripping ends.

### Claim 3 (currently amended)

The fastener-gripping tool of claims 1 and or 2 wherein said primary and secondary members are generally mirrored opposites to each other.

# Claim 4 (currently amended)

The fastener-gripping tool of claim 1 further comprising gripping ends at the extremity-distal to the handles at each extremity of the primary and secondary members.

### Claim 5 (withdrawn)

### Claim 6 (original)

The fastener-gripping tool of claim 4 wherein the primary member is adapted with one central claw and the secondary members is adapted with two claws, one at either side of the primary member's central claw.

### Claim 7 (currently amended)

The fastener-gripping tool of claim 6 wherein said claws have a triangular opening within the inner surfaces of each claw thereby forming a generally square opening between the claws when viewed from above-, and providing and auto-centering grip for a fastener such as a nail or screw.

## Claim 8 (currently amended)

The fastener-gripping tool of claims 1, 5, 6 and or 7 wherein the claw extremities are pointed generally sharply so as to ease picking up a fastener laid onto a surface.

# Claim 9 (currently amended)

The fastener-gripping tool of claim 1 wherein the use thereof is to gather, hold and automatically align a any conventional size fastener such as a nail or screw while driving said fastener, all by means of the auto-centering and auto-sizing features o the present invention.

**CLAIMS LISTING -CLEAN VERSION** 

Appl. #:

10/657,225

Applicant:

MC Ilvenna, Ryan

Filing date:

09/09/2003

Claim 1 (currently amended)

A fastener-gripping tool comprising:

a. a primary and secondary member, both having a handle,

b. a nail pulling central portion,

c. a pair of gripping ends,

d. a claw at each said end,

e. auto-centering and auto-sizing means,

Claim 2 (currently amended)

The fastener-gripping tool of claim 1 wherein said primary and secondary

members are hinged together at a central area thereby providing a rotary motion pivoting

at said central area for aligning the claws at each extremity of the gripping ends.

Claim 3 (currently amended)

The fastener-gripping tool of claim 1 or 2 wherein said primary and secondary

members are generally mirrored opposites to each other.

Claim 4 (currently amended)

The fastener-gripping tool of claim 1 further comprising gripping ends distal to

the handles at each extremity of the primary and secondary members.

### Claim 5 (withdrawn)

### Claim 6 (original)

The fastener-gripping tool of claim 4 wherein the primary member is adapted with one central claw and the secondary members is adapted with two claws, one at either side of the primary member's central claw.

### Claim 7 (currently amended)

The fastener-gripping tool of claim 6 wherein said claws have a triangular opening within the inner surfaces of each claw thereby forming a generally square opening between the claws when viewed from above, and providing and auto-centering grip for a fastener such as a nail or screw.

## Claim 8 (currently amended)

The fastener-gripping tool of claim 1, 5, 6 or 7 wherein the claw extremities are pointed generally sharply so as to ease picking up a fastener laid onto a surface.

### Claim 9 (currently amended)

The fastener-gripping tool of claim 1 wherein the use thereof is to gather, hold and automatically align any conventional size fastener such as a nail or screw while driving said fastener, all by means of the auto-centering and auto-sizing features o the present invention.